

# Enviroboards

## Intumescent Acoustic Jointing Sealant

This Intumescent & Acoustic Sealant is a ready to use halogen free sealant that provides a 4 hour fire barrier combined with excellent sound damping properties. It is ideal for sealing irregular or uneven gaps around service penetrations, door casings and sills, also for sealing fire protection boards and partitioning. Use to seal low movement construction joints where fire rating is required. Can be used to seal joints up to 35mm wide.

### Test Data and Classification

Independently tested to BS EN 1366 Part 4

Complies with BS 476 Part 20

Classification: ISO 11600 – 12.5P

Acoustic properties – Tested to BS EN ISO 140-3:1995

Test Report Nos. 125-76, 77, 79-81



### Directions for use:

Surfaces to be sealed must be clean, dry and free from dust, dirt, frost, grease and other contamination. Cut the cartridge tip and the applicator nozzle to the required diameter and angle, screw nozzle on to cartridge. Apply sealant with applicator gun ensuring good surface contact is achieved by forcing sealant into the joint to be sealed. If necessary, tool within 5 minutes of application using a spatula dipped in soapy water, apply sufficient pressure to ensure good contact of the sealant against the joint surfaces. Clean tools with water immediately after use. Wash hands after use.

### Limitations:

Not to be used in applications subject to permanent water immersion.  
It is always the user's responsibility to determine suitability of use.  
It is not recommended for use in areas subject to abrasion.

### Health and Safety:

Avoid contact with skin and eyes.  
In case of contact with eyes, flush immediately with water and seek medical advice.  
Wear suitable protective clothing and gloves.  
Keep out of reach of children.  
Do not ingest.